



SPECIFICATION	
Model	PTZ22X5APT
Camera	
Image Sensor	1/2.5" Aptina 5.1MP High Performance CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	45°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Auto Flip	Support
Ratio Speed	Support
360° Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	¢ 42x6PCS
IR Range	60m
Auto Control IR LED	PWM
Network	
Network protocol	TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream	5MP@ 15fps
Sub Stream	640*480/480*360
MJPEG	2592*1944/1920*1080/ 1280*720
IE Brower	IE8-11, Google Chrome, Firefox
Interface	
Audio	/
Alarm	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V 2A/3A
POE (Optional)	Power Consumption≤15.4Watts
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)

Weight	4.2Kgs
--------	--------