



SPECIFICATION	
Model NO.	CAM5MPXVAR
Video Output Mode	AHD: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps; TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps
Camera	
Image Sensor	1/2.5" Pixart 5MP CMOS Sensor
Image Resolution	5MP
Effective Pixels	5M:2592*1944 4M:2560*1440
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan
Lens	
Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal
Pixels	5M Pixels
Auto Iris Support	NO
Night Vision	
Infrared LED	42 x 4PCS
Infrared Distance	40M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Camera Features	
Starlight	/
Day/Night	YES
OSD Menu Language	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	DNR
Picture Adjustment	YES
WDR	YES
OSD Support	YES
UTC	YES
Dip Switch	/
General	
Housing	Metal, IP66
Bracket	YES
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Audio	/
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	211(W) x 92(H) x 90(D)mm
Weight	1400g

